



CONCEALED TRAPWAY CADET® 3 FloWise® RIGHT HEIGHT® ELONGATED TOILET

VITREOUS CHINA



CONCEALED TRAPWAY CADET® 3 FloWise® RIGHT HEIGHT® ELONGATED TOILET

☐ 2989.101

- Vitreous china
- Meets definition for HET (High Efficiency Toilet)
- High efficiency (4.8 Lpf/1.28 gpf)
- Meets EPA WaterSense® criteria
- 305mm (12") rough-in
- 16-1/2" rim height for accessible applications
- EverClean® surface inhibits the growth of stain- and odor-causing bacteria, mold, and mildew on the surface
- Features the **Cadet® 3 Flushing System**
- Elongated siphon action jetted bowl with smooth-sided, concealed trapway
- Generous 9" x 8" water surface area
- PowerWash® rim scrubs bowl with each flush
- Oversized 3" flush valve
- Chrome trip lever
- Includes top mounting, plastic Slow-Close seat and cover with easy lift-off feature for simple removal and attachment for cleaning, packed with bowl
- 2 color-matched bolt hole covers
- Lifetime warranty on chinaware, 5 year warranty on all mechanical parts, and 1 year warranty on seat

- ☐ **2989.813** Same as above except with trip lever on right hand side

- ☐ **3075.000** Right Height® Elongated Bowl with Seat

- ☐ **4000.101** Tank

- ☐ **4000.813** Tank with right hand trip lever

Nominal Dimensions:

768 x 400 x 781mm

(30-1/4" x 15-3/4" x 30-3/4")

Fixture and toilet seat only, supply by others

Compliance Certifications -

Meets or Exceeds the Following Specifications:

- ASME A112.19.2-2008/CSA B45.1-08 for Vitreous China Fixtures
- US EPA WaterSense® Specification for HET's

To Be Specified:

- ☐ Color: ☐ White
☐ Supply with stop:



MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES-CHECK LOCAL CODES.



SEE REVERSE FOR ROUGHING-IN DIMENSIONS



CADET® 3
Flushing System



VITREOUS CHINA



Revised 1/13